MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard. 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Note: Blank spaces are not permitted. If any item is not applicable, or no

IDENTITY (As Used on Label and List)

| SUN CL | EAR | information is available, the space must be marked to indicate th | | | | | |
|---|---|---|--------------------------|------------|--------------|--|--|
| Europe: EINECS# 231-545-4 EIN | ECS# 246-368-8 | CAS# 7631-86-9 Silicon Oxio B EINECS# Nations registration of dan | 238-878 | 3-4 |)-7 | | |
| Section I | | | | | | | |
| Manufacturer's Name SOLARSUN, INC. | Emergency Telephone Number 631 941-4096 | | | | | | |
| Address (Number, Street, City, State, and Zip Code) FLOWERFIELD INDUSTRIAL PARK, SETAUKET NY 11733-1503 USA ST. JAMES, NY 11780 | | Telephone Number for Information 631 941-4096 | | | | | |
| | | Date Prepared 01/01/16 | | | | | |
| | | Signature of Preparer (optional) | | | | | |
| Section II Hazardous Ingredients/Id | dentity Informat | ion | | | | | |
| Hazardous Components (Specific Chemical Ide | entity; Common Nar | mes(s) OSHA PEL ACGIG | TLV Ot | her Limits | % (optional) | | |
| NONE / Currently not classified according to EEC Directives. | | | | | | | |
| Section III Ingredients/Identity Info | rmation | | | | | | |
| Components (Specific Chemical Identity | y; Common Nam | es(s) | | | | | |
| Alumina (also known as aluminum oxide and/or boehmite) CAS# 1344-28-1 | | | | | | | |
| Siica (also known as , Amorphous silicon and/or sand) CAS# 7631-86-9 | | | | | | | |
| Silicon Oxide (also known as Quartz (Si | O2) CAS# 14808 | 8-60-7 | | | | | |
| FOOTNOTE: NE = NOT ESTABLISHED NR = NOT REQUIRED NA = NOT APPLICABLE | | | | | | | |
| Section IV Physical/Chemical Char | acteristics | | | | | | |
| Boiling Point 100C / 212F | (WATER) | Specific Gravity (H2O=1) | Specific Gravity (H2O=1) | | | | |
| Vapor Pressure (mm Hg.) 20C / 68F | WATER 720MM | Percent, Volatile By Volume (9 | %) H2O | 80% | | | |
| Vapor Density (AIR = 1) | 1 | Evaporation Rate (Butyl Acetate = 1) | SLOWER | | ∃R | | |
| Solubility in Water: | DILUTABLE | Freeze Point OC / 3 | | 0C / 32 | F | | |
| Appearance and Odor: CLOUDY WHITE LI | QUID; NO ODOF | 3 | | | | | |
| Section V Fire and Explosion Haza | rd Data | | | i | | | |
| Flash Point: NON-COMBUSTIBLE | | Flammable Limits N.A. | NEL | | UEL | | |
| Extinguishing Media: USE MEDIA PROPER | TO THE PRIMAR | Y CAUSE OF THE FIRE | | | | | |
| Special Fire fighting Procedures: N.A. | | | | | | | |
| Unusual Fire and Explosion Hazards: N.A. | | | | | | | |

| Section VI R | EACTIVITY DAT | A | | | | | |
|--|--------------------|--------|----------------------------|------------------------|--|--|--|
| Stability | Unstable | | Conditions to Avoid N.A. | nditions to Avoid N.A. | | | |
| | Stable | Х | | | | | |
| Incompatibility (Materials to Avoid): Alkaline materials will cause gellation | | | | | | | |
| Hazardous Decomposition of Byproducts N.A. | | | | | | | |
| Hazardous Polymerization | May Occur | | Conditions to Avoid | | | | |
| | Will Not Occur | Х | | | | | |
| Section VII Health and Hazard Data | | | | | | | |
| Route(s) of Entry: Inhalation: No ill effects Skin: No ill effects Ingestion No ill effects | | | | | | | |
| Health Hazards (Acute and Chronic) INHALATION: NONE SKIN CONTACT: NONE. EYE CONTACT: Direct contact may while spraying Sun Clear wear a simple gauze mask. | | | | | | | |
| Carcinogenicity: | | NTP | IARC: NO OSHA Regulated: 1 | 10 | | | |
| Toxicity Information: Amorphous Silicon Dioxide: N/A | | | | | | | |
| Aluminum Oxide: N/A | | | | | | | |
| Signs and Symptoms of Exposure N.A. | | | | | | | |
| Medical Conditions Generally Aggravated by Exposure N.A. | | | | | | | |
| Emergency and First Aid Procedures: EYE CONTACT : Promptly flush eyes with water. Mildly acid, pH 5; Consult physician if splashed in eyes. | | | | | | | |
| TRANSPORT INFORMATION - Non-hazardous for road, sea and airfreight. | | | | | | | |
| Section VIII Precautions for Safe Handling and Use | | | | | | | |
| Steps to Be Taken in Case Material is Released or Spilled: Wash down spills with water. Waste Disposal Method: Sewer or landfill. | | | | | | | |
| | | | | | | | |
| Precautions to Be Taken in Handling and Storing: Temperature; max. 60C/140F, min. 2C/35F. Keep from freezing, product may coagulate. | | | | | | | |
| Other Precautions: Do not store at elevated temperatures. Drums may rupture from excessive pressure (water and air). | | | | | | | |
| Section IX Control Measures | | | | | | | |
| Respiratory Protection (Specify Type) None required if good ventilation is used. Other wise wear MESA/NIOSH approved respirator suitable for concentrations encountered. | | | | | | | |
| Ventilation L | ocal Exhaust: None | e requ | red Special: | | | | |
| N | Mechanical: None r | equire | Other: | | | | |
| Protective Gloves: No Eye protection: Safety glasses with side shield. | | | | nield. | | | |
| Other Protective Clothing or Equipment: Wear a simple gauze mask while spraying. | | | | | | | |
| Hygienic Practices | | | | | | | |