
HPF JD360 Destratifier Fan Ring Kits and HPF Portable Pumps

Pairing J&D's JD360 Destratifier Fans with High Pressure Fog Ring Kits and HPF Portable Pumps, you can create an ideal growing climate in your greenhouse by generating the perfect balance of temperature, humidity, and air movement.



-HPF Ring Kit

- Customize your cooling with three nozzle sizes to choose from
 - .006 GPM (8)
 - .015 GPM (8)
 - .039 GPM (8)
- Stainless-steel for long life and corrosion resistance
- ¾" slip lock connector for easy installation
- Chemical-resistant nylon hardware for attaching ring to fan



mer Portable Pullips -

Portable and self-contained

- %" slip lock connector for easy installation
- Includes E micron E" commercial water filter w
- Includes 5 micron 5" commercial water filter with standard ¾" GHT hose fitting
- Attached 10' cord with 3-prong plug pre-wired for 110 Volts
- Raised rubber feet to reduce vibration and minimize sound
- 0.15-1.0 GPM models are compatible with optional Smart Phone Controller



Ring Kit Part# Description SS2218 JD360 Fog Ring Kit, 22" with (8).006 GPM Nozzles = .048 GPM SS2228 JD360 Fog Ring Kit, 22" with (8).015 GPM Nozzles = .120 GPM SS2238 JD360 Fog Ring Kit, 22" with (8).039 GPM Nozzles = .312 GPM

						Minimum-Maximum # of		
Pump						JD360 F	ling Kits po	er Pump
Part#	GPM	HP	Volts	Hz	Amps	SS2218	SS2228	SS2238
JD14241	0.15	1/4	110	60	1.38	3-5	1-2	0
JD14242	0.3	1/4	110	60	2.15	6-9	3-4	1
JD14122	0.5	1/2	110	60	5.8	10-19	4-7	2-3
JD14124	1.0	1	110	60	9.2	20-39	8-15	3-6
JD14126*	2.0	2	110	60	16.5	40-55	16-23	6-9

	Description					
JD62200*	Smart Phone Pump Controller					

* 2.0 GPM model not compatible with Smart Phone Pump Controller

Water Quality Requirements

Thorough water testing and treatment of your intended water supply by qualified water treatment professionals is required to minimize mineral deposits and corrosion that may block or erode nozzles.

Shown are the basic parameters required of your water supply. Additional requirements by your water treatment professionals may be justified. Damage or clogging of nozzles or other elements of J&D's High Pressure Fogging system due to insufficiently treated water will not be covered by warranty.

Test	Required Parameters	
Hardness	Less than 7gpg	
	(120 parts per million or milligrams per liter)	
PH	7.0 or higher	
Dissolved Metals	Listed are the most common and problematic.	
	Consult with your water specialist on what additional dissolved metals you may need to correct.	
	Iron - Less than 0.3 parts per million	
	Manganese - Less than 0.05 parts per million	
TDS	Less than 500 milligrams per liter	
(Total Dissolved Solids)		

▲ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.